# SAFETY DATA SHEET



## Section 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Trade name or designation

of the mixture

Super Sap ONE Epoxy Resin

**Identification Number** Not applicable.

Registration number -

Synonyms None.

Date of first issue 05-March-2015

Version number 0
Revision date Supersedes date -

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Liquid epoxy resin for compositions for the building and civil engineering industries e.g. flooring

compounds, primers, adhesives, mortars, joints and grouts. Offshore & Marine applications.

Uses advised against Not available.

Details of the supplier of the safety data sheet

Company name Entropy Resins
Address Entropy Resins

30621 San Antonio St. Hayward, CA 94544 USA

Contact person: Diosdado Rey Banatao

-

Telephone info@entropyresins.com

**e-mail** 24/7 Emergency Hotline : 1 (760) 476-3962 **Emergency telephone** Global Response Access Code: 333178

Number

### **Section 2: Hazards identification**

#### Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification Xi;R36/38, R43, N;R51-53

The full text for all R-phrases is displayed in section 16.

### Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

Skin corrosion/irritation Category 2 Causes skin irritation.

Serious eye damage/eye irritation Category 2 Causes serious eye irritation.

Skin sensitization Category 1 May cause an allergic skin

reaction.

**Environmental hazards** 

Hazardous to the aquatic environment - Category 2 Toxic to aquatic life with long

long-term hazard lasting effects.

**Hazard summary** 

**Physical hazards** Not classified for physical hazards.

**Health hazards** Irritating to eyes and skin. May cause sensitisation by skin contact.

**Environmental hazards** Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

**Specific hazards** Ingestion may cause irritation and malaise.

Main symptoms Symptoms include itching, burning, redness, and tearing of eyes. Rash.

Label elements

Super Sap ONE Epoxy
SDS Code: SDS\_11\_ONE03
Version No.: 01
Revision date: 05-March-2015
1 / 8

### Label according to Regulation (EC) No. 1272/2008 as amended

Reaction product: Contains:

bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)



Warning Signal word

**Hazard statements** Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to

aquatic life with long lasting effects.

**Precautionary statements** 

Prevention Wear protective gloves. Wear eye/face protection. Avoid breathing mist/vapours/spray. Wash

thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Collect spillage. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Response

> Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store as indicated in Section 7.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

Other hazards Contains epoxy constituents. May produce an allergic reaction.

No other specific acute or chronic health impact noted.

# Section 3: Composition/information on ingredients

#### **Mixture**

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Reaction product:	50-80	25068-38-6 500-033-5	-	603-074-00-8	

resin (number average molecular

weight  $\leq$  700)

Classification: **DSD:** Xi;R36/38, R43, N;R51-53

CLP: Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, Aquatic Chronic 2;H411

Oxirane, mono [(C12-14alkyloxy)methyl derivatives

Classification:

10-20

**DSD:** Xi;R36/38, R43, N;R51-53

CLP: Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, Aquatic Chronic 2;H411

68609-97-2

Glycerine Carbonate <10 931-40-8

Classification: DSD:

CLP:

Benzyl alcohol 603-057-00-5 <10 100-51-6

202-859-9

Classification: **DSD:** Xn;R20/22

> CLP: Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Irrit. 2;H315, Skin Sens. 1;H317, Acute Tox.

4;H332, Aquatic Chronic 2;H411

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The full text for all R- and H-phrases is displayed in section 16.

SDS UK Super Sap ONE Epoxy SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015 2/8

#### Section 4: First aid measures

**General information** 

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### Description of first aid measures

Inhalation

Move to fresh air. Get medical attention if any discomfort occurs.

Skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort occurs. If ingestion of a large amount does occur, call a poison control centre immediately.

Most important symptoms and effects, both acute and delayed Symptoms include itching, burning, redness, and tearing of eyes. Rash.

Indication of any immediate

Treat symptomatically.

medical attention and special treatment needed

## Section 5: Firefighting measures

General fire hazards

May burn, but does not ignite readily.

**Extinguishing media** 

Suitable extinguishing

media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in

the workplace.

Special firefighting

procedures

Water runoff can cause environmental damage.

#### Section 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Avoid contact with skin and eyes. See Section 8 for personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

SDS.

**Environmental precautions** 

Do not contaminate water. Avoid release to the environment. Refer to special instructions/safety

data sheets.

Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Prevent product from entering drains.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13.

Reference to other sections

See Section 8 for personal protective equipment.

For waste disposal, see Section 13.

### Section 7: Handling and storage

Precautions for safe handling

Provide adequate ventilation. Persons with epoxy allergy should not work with this product. Follow special provisions related to work with this material. Avoid contact with skin and eyes. Wear respiratory protection during operations where spraying or misting occurs. Use Personal Protective Equipment recommended in section 8 of the MSDS. Change contaminated clothing. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials.

SDS UK Super Sap ONE Epoxy SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015 3/8 Specific end use(s)

Compositions for the building and civil engineering industries e.g. flooring compounds, primers,

adhesives, mortars, joints and grouts.

### Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits No exposure limits noted for the ingredient(s).

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

DNFI

Not available.

**PNEC** 

Not available.

**Exposure controls** 

Appropiate engineering

controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

**General information** Follow special provisions related to work with this material. Personal protective equipment should

be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Private clothes and working clothes should be kept separately. Make sure

to provide adequate control by applying the "COSHH Essentials" procedure.

Eye/face protection

Skin protection - Hand protection

Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is

advisable. Use protective gloves made of: Polyethylene/Ethylene Vinyl Alcohol (PE/EVAL).

Suitable gloves can be recommended by the glove supplier.

- Other Protection suit must be worn. Seek advice from local supervisor.

Wear approved safety goggles.

Respiratory protection No personal respiratory protective equipment normally required. In case of inadequate ventilation

or risk of inhalation of vapours, use suitable respiratory equipment with gas filter (type A2).

Observe special requirements if using the product for spraying.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking and/or smoking. Routinely wash work clothing to remove

contaminants. Discard contaminated footwear that cannot be cleaned.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

#### Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Clear/pale yellow liquid. **Appearance** 

Physical state Liquid. Form Liquid.

> Clear/pale yellow. Colour

Odour Slight.

Not available. **Odour threshold** Not applicable. pН Melting point/freezing

point

Not available.

Boiling point, initial boiling point, and boiling range

Not available.

> 200 °C (> 392 °F) Flash point **Auto-ignition temperature** Not applicable. Flammability (solid, gas) Not available.

Flammability limit - lower

Not available.

(%)

Not available. Flammability limit - upper

(%)

SDS UK Super Sap ONE Epoxy SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015

Oxidising properties

Explosive properties

Not applicable.

Explosive properties

Not applicable.

Vapour pressure

Vapour density

Evaporation rate

Relative density

Not applicable.

Not applicable.

Not applicable.

Not applicable.

**Density** 1100 - 1200 kg/m3 @ 25 °C

Solubility Negligible.

Partition coefficient Not available.

(n-octanol/water)

**Decomposition** Not available.

temperature

Bulk densityNot applicable.Pour pointNot applicable.ViscosityNot available.VOC (Weight%)Not available.Percent volatileNot available.

Other data

Dynamic viscosity 8 - 13 Pa·s @ 25 °C

Other information No relevant additional information available.

### Section 10: Stability and reactivity

Reactivity Reacts with oxidising agents.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

Polymerises exothermically with amines, mercaptens and Lewis acids at ambient temperature and above. Polymerises in contact with bases ( eg caustic soda), ammonia, primary and

secondary amines, alcohol's and acids.

Conditions to avoid Contact with incompatible materials. Heat, flames and sparks. Avoid temperatures exceeding the

flash point.

Incompatible materials Caustic soda. Strong oxidising agents.

**Hazardous decomposition** 

products

None under normal temperatures and pressures.

# **Section 11: Toxicological information**

General information Persons with epoxy allergy should not work with this product. Persons with pre-existing skin

disorders may be more susceptible to the effects of the product.

Information on likely routes of exposure

**Ingestion** May cause discomfort if swallowed.

**Inhalation** Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Symptoms** Symptoms include itching, burning, redness, and tearing of eyes. Rash.

Information on toxicological effects

Acute toxicity Ingestion may cause irritation and malaise.

Product Test results

Super Sap ONE Epoxy Resin (Mixture)

Acute Oral LD50 Rat: > 10000 mg/kg

**Skin corrosion/irritation** May cause redness and pain.

Serious eye damage/eye

irritation

Exposed may experience eye tearing, redness, and discomfort.

Respiratory sensitization Not available.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** Positive in vitro, but negative in vivo assays.

CarcinogenicityNot classified.Reproductive toxicityNot available.Specific target organNot available.

toxicity - single exposure

Super Sap ONE Epoxy
SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015 5 / 8

Specific target organ toxicity - repeated exposure

Not available.

**Aspiration hazard** 

Mixture versus substance information

Not applicable.

No additional adverse health effects noted.

Other information Not available

# Section 12: Ecological information

No toxicity data noted for the ingredient(s). **Toxicity** The product is not readily biodegradable. Persistence and

degradability

**Bioaccumulative potential** Has the potential to bioaccumulate.

Mobility The product is insoluble in water and will sediment in water systems.

Not available. **Environmental fate -**

Partition coefficient

Not available. Mobility in soil Results of PBT and Not available. vPvB assessment

Other adverse effects Toxic to aquatic life with long lasting effects.

### **Section 13: Disposal considerations**

Waste treatment methods

Residual waste Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

EU waste code 16 05 08\*

Disposal methods/information This material and its container must be disposed of as hazardous waste. Do not discharge into

drains, water courses or onto the ground. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and

material characteristics at time of disposal.

### **Section 14: Transport information**

**ADR** 

**UN number** UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (Reaction product:

bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

Transport hazard class(es) Subsidiary class(es) - III Packing group Yes **Environmental hazards** E **Tunnel restriction code** 9

Labels required Not available.

Special precautions for user

RID

Environmentally hazardous substance, liquid, n.o.s. (Reaction product: UN number

bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)) **UN proper shipping name** 

Transport hazard class(es) - 111 Subsidiary class(es) Yes Packing group

Not available. **Environmental hazards** 

Labels required

Special precautions for user UN3082

ADN

Environmentally Hazardous Liquid, N.o.s. (Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)) **UN number** 

**UN proper shipping name** - 111

Transport hazard class(es) Yes. Subsidiary class(es)

Packing group

**Environmental hazards** 

Labels required

SDS UK Super Sap ONE Epoxy SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015

6/8

Special precautions for user Not available.

IATA

**UN** number UN3082

Environmentally hazardous substance, liquid, n.o.s. (Reaction product: **UN proper shipping name** 

bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

Transport hazard class(es) - 111 Subsidiary class(es) Packing group Yes. **Environmental hazards** 

Not available. Labels required

Special precautions for user

**IMDG** UN3082


Environmentally hazardous substance, liquid, n.o.s. (Reaction product: UN number

UN proper shipping name bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

Transport hazard class(es) - 111 Subsidiary class(es) Yes. Packing group 9 Marine pollutant F-A, S-F Labels required Not available.

EmS No.

Special precautions for user



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

# **Section 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture **EU Regulations** 

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V

Directive 96/61/EC concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution **Emission Registery (EPER)** 

Not listed.

Regulation (EC) No. 1907/2006, Article 59(1). Candidate List

Not listed.

Other regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work. This Safety Data Sheet complies

with the requirements of Regulation (EC) No 1907/2006 as amended.

**National regulations** 

**Chemical Safety Assessment** No Chemical Safety Assessment has been carried out.

Super Sap ONE Epoxy SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015 7/8

SDS UK

### **Section 16: Other information**

**List of abbreviations** DNEL: Derived No-Effect Level.

PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioccumulative.

References Not available.

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if

available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-phrases under Sections 2 to 15 R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

**Training information** 

Not available.

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available.

Super Sap ONE Epoxy
SDS Code: SDS\_11\_ONE03 Version No.: 01 Revision date: 05-March-2015 8 / 8