


TECHNICAL DATASHEET

Flash Tape 2



MALLENBOUW | COMPOSITEN | LIJMEN

Flashtape 2

Adhesive Tape

Flashtape 2

Flashtape 2 is an adhesive tape and ideally suited for high temperature applications.

Features and Benefits

- Polyester tape backed with a fully cured, pressure sensitive adhesive.
- Excellent temperature and pressure resistance.
- Strips easily after use

PROPERTIES

Table 1 | Product Properties

Property	Description
Maximum Cure Temperature	400°F (204°C)
Total thickness	0.003 in (72 µm)
Adhesive thickness	0.002 in (50 µm)
Tape thickness	0.001 in (25 µm)
Elongation at break	100%

Table 2 | Product Availability

Property	Description
Color	Blue
Adhesive	Silicone and Acrylic
Carrier	Polyester
Standard width	1, 2 in (25, 50 mm)
Standard length	72 yd. (66 m)

Storage

No special storage conditions

HEALTH & SAFETY

Please refer to the product SDS for safe handling, personal protective equipment recommendations and disposal considerations.

DISCLAIMER: The data and information provided in this document have been obtained from carefully controlled samples and are considered to be representative of the product described. Solvay does not express or imply any guarantee or warranty of any kind including, but not limited to, the accuracy, the completeness or the relevance of the data and information set out herein. Because the properties of this product can be significantly affected by the fabrication and testing techniques employed, and since Solvay does not control the conditions under which its products are tested and used, Solvay cannot guarantee the properties provided will be obtained with other processes and equipment. No guarantee or warranty is provided if the product is adapted for a specific use or purpose. Solvay declines any liability with respect to the use made by any third party of the data and information contained herein. Solvay has the right to change any data or information when deemed appropriate. All trademarks are the property of their respective owners. ©2019, Solvay. All rights reserved.

Solvay

Composite Materials HQ
4500 McGinnis Ferry Rd
Alpharetta, GA 30005-3914 USA

TDS Flashtape 2_2019_08_29

**SOLVAY**

asking more from chemistry®